

DIGRUTT

Desarrollos 3D, matricería y moldeo por inyección

Tuberías de PEAD

Tendidos subterráneos para
redes de agua potable urbana
e interurbana



Formas de presentación

En bobinas

En tramos

Diámetro mm	Espesor nominal de pared							
20	2.8	2.3	2.0	x	x	x	x	x
25	3.5	2.8	2.3	2.0	x	x	x	x
32	4.4	3.6	2.9	2.4	2.0	x	x	x
40	5.5	4.5	3.7	3.0	2.4	2.0	x	x
50	6.9	5.6	4.6	3.7	3.0	2.4	2.0	x
63	8.6	7.1	5.8	4.7	3.8	3.0	2.5	2.0
75	10.3	8.4	6.8	5.6	4.5	3.6	2.9	2.3
90	12.3	10.1	8.2	6.7	5.4	4.3	3.5	2.8
110	15.1	12.3	10.0	8.1	6.6	5.3	4.2	3.4
125	17.1	14.0	11.4	9.2	7.4	6.0	4.8	3.9
140	19.2	15.7	12.7	10.3	8.3	6.7	5.4	4.3
160	21.9	17.9	14.6	11.8	9.5	7.7	6.2	4.9
180	24.6	20.1	16.4	13.3	10.7	8.6	6.9	5.5
200	27.4	22.4	18.2	14.7	11.9	9.6	7.7	6.2